



EDGE® SAWDUST SIDE DISCHARGE BUCKET

The EDGE sawdust side discharge buckets are a “must have” for many farming applications. The sawdust bucket has a beater to help prevent the bridging of materials.

OPERATIONAL BASICS

The EDGE sawdust side discharge buckets offers discharge from both sides of the machine. This attachment is perfect for large farms with multiple stalls allowing the operator to quickly lay soft and fresh bedding. The EDGE sawdust side discharge bucket is available in three sizes: 60” (1524 mm), 72” (1829 mm), and 84” (2133 mm). This unit comes complete with hoses and flat face couplers.



SPECIFICATION

| Model | Weight (lbs/kg) | Overall Width (in/mm) | Hyd. Req. (gpm/lpm) | Cap. (cf/cm) |
|-------|-----------------|-----------------------|---------------------|--------------|
| SAW60 | 910/412.8 | 61/1550 | 12-30/45-113 | 45/1.27 |
| SAW72 | 1080/489.9 | 73/1854 | 12-30/45-113 | 54/1.53 |
| SAW84 | 1250/567.0 | 85/2159 | 12-30/45-113 | 63/1.78 |

FEATURES

- Beater helps prevent time-consuming bridging problems
- Left or right side discharge
- Large capacity means less refilling

| | Radial Skid Loaders | | | | | | | Vertical Skid Loaders | | | Track Loaders | | | Articulated Loaders | | | |
|---|---------------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------------------|---------------|----------------|------------------|------------------|------------------|---------------------|-----|-------------|-------------|
| Machine Compatibility Gehl / Mustang | 3640E/ 2026 | R135/ 1350R | R150/ 1500R | R165/ 1650R | R190/ 1900R | R220/ 2200R | R260/ 2600R | V270/ 2700V | V330 3300V | V400/ 4000V | RT175/ 1750RT | RT210/ 2100RT | RT250/ 2500RT | 340 | 540 | 650/ 608 | 750/ 708 |
| *Sawdust Side Dis. Bkt. | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | |

*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment