



EDGE® ROTO TILLER

Perfect for seedbed preparation or other landscape functions, the EDGE roto tiller is designed for breaking up clumps and mixing compost or other materials into existing soil.

OPERATIONAL BASICS

The design of the unit allows for operation in a forward or reverse motion. Two EDGE roto tiller models are available to cover working widths of 52" (1320 mm) or 68" (1727 mm). Both models come complete with a hoses, a hose saver kit and couplers.



SPECIFICATIONS

Model	Weight (lbs/kg)	Hyd. Req. (in/mm)	No. of Tines	Digging Depth (in/mm)	Working Width (in/mm)	Overall Width (in/mm)
TL52	600/272	12-40/45-151	28	6/152	52/1320	68/1727
TL68	695/315	15-40/57-151	36	6/152	68/1727	78/1981

FEATURES

- Ideal attachment for landscape and agricultural land preparation
- Unit allows for operation in a forward or reverse motion
- Available in 52" (1320 mm) and 68" (1727 mm) widths

Machine Compatibility Gehl / Mustang	Radial Skid Loaders							Vertical Skid Loaders			Track Loaders			Articulated Loaders			
	3640E/ 2026	R135/ 1350R	R150/ 1500R	R165/ 1650R	R190/ 1900R	R220/ 2200R	R260/ 2600R	V270/ 2700V	V330/ 3300V	V400/ 4000V	RT175/ 1750RT	RT210/ 2100RT	RT250/ 2500RT	340	540	650/ 608	750/ 708
*Roto Tiller	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆

*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment