



SKID STEER LOADER

1050R

PREVIEW

KEY FEATURES

- ▲ Lowest ROPS Height in the Industry
- ▲ NEW Multi-Function, Color Display
- ▲ NEW Fuel Cap & Key
- ▲ NEW "Push to Operate" Logic common to other Mustang Skid Steers
- ▲ Improved Fuel Filter Location/Access
- ▲ Heavier Duty Belly Pan - Access Panel
- ▲ All other Features, Options and Controls common with prior 2026

KEY SPECIFICATIONS

- ▲ Rated Operating Capacity of 1,050 lbs. (476 kg)
- ▲ Yanmar 34.7 hp (25.5 kW) Final Tier IV Engine
- ▲ 108.1" (2796) Height to Hinge Pin
- ▲ 48.4" (1229 mm) Overall Width
- ▲ 70.3" (1786 mm) Height to top of ROPS
- ▲ 4,000 lbs. (1814 kg) Operating Weight



SKID STEER LOADER



1050R

SPECIFICATIONS

DIMENSIONS	Overall Operating Height - Fully Raised (mm)	139.6" (3546)
	Height to Hinge Pin - Fully Raised (mm)	108.1" (2746)
	Overall Height to Top of ROPS (mm)	70.3" (1786)
	Overall Length with Bucket (mm)	114" (2896) w/ 55" Bucket
	Dump Angle at Full Height	42°
	Dump Height (mm)	84.5" (2146)
	Dump Reach at Full Height (mm)	22.8" (579)
	Rollback at Ground	29°
	Rollback Angle at Full Height	99°
	Seat to Ground Height (mm)	32.6" (828)
	Wheelbase (mm)	34.5" (876)
	Overall Width - Less Bucket (mm)	48.4" (1229)
	Bucket Width (mm)	55" (1404)
	Ground Clearance to Chassis (mm)	6.0" (152)
	Overall Length - Less Bucket (mm)	88.9" (2258)
	Departure Angle	26°
	Clearance Circle - Front w/ Bucket (mm)	69.4" (1763)
Clearance Circle - Front w/o Bucket (mm)	44.1" (1120)	
Clearance Circle - Rear (mm)	54.1" (1374)	
Standard Specification Tire Size	27x8.5x15 HD	
CAPACITY / WEIGHTS	Rated Operating Capacity (kg)	1,050 lbs. (476)
	Rated Op. Capacity with Opt. Counterweight (kg)	1,175 lbs. (533)
	Fuel Tank (L)	10.4 gal. (39.4)
	Travel Speed - Maximum (km/hr)	5.9 mph (9.5)
	Operating Weight - Approximate (kg)	4,000 lbs. (1814)
ENGINE	Make	Yanmar
	Model	3TNV88C-KMS Tier IV
	Gross Power (kW) @ rpm	34.7 hp (25.5) @ 2800
	Net Power (kW) @ rpm	33.1 hp (24.7) @ 2800
	Maximum Torque (Nm) @ rpm	80 ft.-lbs. (108) @ 1680
	Displacement (L)	100 cu. in. (1.6)
ELECTRICAL SYSTEM	Battery (CCA)	12-volt (675)
	Starter (kW)	12-volt (2.3)
	Alternator	40-amp
HYDRAULICS	Auxiliary Hydraulics - Standard (L/min)	14.5 gpm (55)
	High-Flow Auxiliary Hydraulics - Option (L/min)	N/A
	Reservoir Capacity (L)	8 gal. (30.3)

STANDARD FEATURES

- ▲ Mustang Hands Only Controls
- ▲ Hand/Foot Controls
- ▲ Auxiliary Hydraulics
- ▲ High-Back Adjustable Seats
- ▲ Foot and Hand Throttles
- ▲ Multi-Function Color Display w/ Full Instrumentation
- ▲ Integral Access Plate (removable)
- ▲ Operator Restraint Bar
- ▲ ROPS/FOPS Level II Overhead Guard
- ▲ Work Lights - Front and Rear
- ▲ Multi-Tach® Attachment Mounting System
- ▲ Anti-Vandalism Protection
- ▲ Brake Control (Auto / Manual)
- ▲ Hydraloc™ Safety System
- ▲ Hydrostatic Drive - Servo
- ▲ Lift Arm Support Device

OPTIONAL FEATURES

- ▲ Engine Auto-Shutdown System
- ▲ Engine Block Heater
- ▲ Suspension Seat - Mechanical
- ▲ Cab Enclosure
- ▲ Horn
- ▲ Sound Reduction Material
- ▲ Back-Up Alarm
- ▲ Selectable Self-Leveling Hydraulic Lift Action
- ▲ Side Windows
- ▲ Swing Out Door
- ▲ Cab Heater
- ▲ Fenders
- ▲ Rear Window Wiper
- ▲ Rear Counterweight (+125 lbs. ROC)

SPECIFICATIONS ARE PRELIMINARY

Mustang reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Mustang reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

MUSTANG
mustangmfg.com

Find us on
Facebook

MUSTANG MFG.

147 Indiana Avenue, West Bend, WI 53095

Phone: (262) 334-9461