



EDGE® DOZER BLADES

So simple, yet so vital, the EDGE dozer blade has stood the test of time. You'll find different blades for a variety of settings, conditions, and uses, including scraping and leveling, and flood cleanup.

OPERATIONAL BASICS

EDGE dozer blades are available in sizes ranging from 72" (1828 mm) to 108" (2743 mm) and feature 30 degree right and left angling, and 10 degree right and left tilt. EDGE dozer blades have replaceable cutting edges, hoses and flat-faced couplers included. Control harness adapters are sold separately. Dozer's must be ordered with an adapter. *Note: EDGE dozer blades are not to be used for snow removal.*



SPECIFICATIONS

| Model | Weight (lbs/kg) | Straight Path (in/mm) | Angled Path (in/mm) | Angle (degrees) | Tilt (degrees) | Height (in/mm) |
|-------|--------------------|--------------------------|------------------------|--------------------|-------------------|-------------------|
| DB72 | 1360/616.9 | 72/1828 | 63.5/1612 | 30 | 10 | 24/609 |
| DB84 | 1453/659.1 | 84/2134 | 74.2/1884 | 30 | 10 | 24/609 |
| DB96 | 1507/683.6 | 96/2438 | 84.7/2151 | 30 | 10 | 24/609 |
| DB108 | 1570/712.2 | 108/2743 | 93.5/2374 | 30 | 10 | 24/609 |

FEATURES

- Heavy duty blade with 30 degree angle and 10 degree tilt
- Electro-hydraulic angle and tilt right from the cab
- Available in sizes from 72" (1828 mm) and 108" (2743 mm)

| | Radial Skid Loaders | | | | | | | Vertical Skid Loaders | | | Track Loaders | | |
|---|---------------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------------------|---------------|----------------|------------------|------------------|------------------|
| Machine Compatibility Gehl / Mustang | 3640E/ 2026 | R135/ 1350R | R150/ 1500R | R165/ 1650R | R190/ 1900R | R220/ 2200R | R260/ 2600R | V270/ 2700V | V330 3300V | V400/ 4000V | RT175/ 1750RT | RT210/ 2100RT | RT250/ 2500RT |
| *Dozer Blades | | | | + | + | + | + | * | + | • | + | + | + |

*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment

