

TX-408

TELESCOPIC HANDLER



KEY FEATURES

- ✓ 7.6 m Lifting Height
- ✓ 4 Ton Capacity
- ✓ 4 Equal Wheels
- ✓ 4 Wheel Steering
- ✓ 3 Steering Modes
- ✓ 4.23 m Reach
- ✓ Torque Converter Transmission
- ✓ Perkins 94 hp Engine
- ✓ 38 cm Ground Clearance
- ✓ High Tilting Angle 27°



SPECIFICATIONS

		METRIC	IMPERIAL
CAPACITIES	Maximum Capacity	4000 kg	8818 lbs
	Maximum Lift Height	7.6 m	24' 11"
	Maximum Reach	4.23 m	13' 11"
ENGINE	Manufacturer	Perkins	
	Model	1104D-44T Stage 3A	
	Number of Cylinders - Capacity	4 - 4400 cm ³	
	Power	94 hp	70 kW
	Torque	392 Nm	289 ft.-lbs.
HYDRAULICS	Pump Type	Gear Pump	
	Pump Flow	86 L/min	22.7 gal/min
	System Pressure	250 bar	3626 psi
	Hydraulic Tank Capacity	120 L	38 gal
COMPONENTS	Transmission	Torque Converter	
	Maximum Travel Speed	28 kph	17.4 mph
	Selective Steering	4-Wheel 2-Wheel Crab	
	Hydraulically Actuated Brakes	Standard	
	Parking Brake	Manual	
	Axle Manufacturer	Dana	
GENERAL SPECIFICATIONS	Overall Length of Carriage	4.93 m	16' 2"
	Overall Width	2.38 m	7' 10"
	Overall Height	2.59 m	8' 6"
	Wheelbase	2.58 m	8' 6"
	Ground Clearance	0.38 m	12' 3"
	Overall Cabin Width	0.85 m	2' 10"
	Frame Outer Turning Radius	3.9 m	12' 10"
	Unladen Weight (w/ forks)	8140 kg	17,946 lbs
	Standard Forks	1200x125x45	

STANDARD FEATURES

- Enclosed cab, FOPS/ROPS Level 2
- Road lights
- Stability simple hydraulic cut-off
- Battery cut-off
- Cyclonic pre-filter

OPTIONAL FEATURES

- Hydraulic line for attachments
- Heater
- Air conditioning
- Windscreen protection grid
- Aggravating movement cut-off
- Front & rear working lights



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517

