

R134

SKID LOADER

GEHL®



KEY FEATURES

- ✓ PowerView® Boom Lift Arm - Radial
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS
- ✓ Dual T-Bar
- ✓ Cushion Seat
- ✓ Battery Charge Indicator Lamp
- ✓ Hourmeter
- ✓ Vandalism Lock Provisions - Fuel and Engine Cover

KEY SPECIFICATIONS

- ✓ Operating capacity (50%) – 612 kg (1,340 lbs.)
- ✓ Overall height to top of ROPS – 1826 mm (71.9")
- ✓ Gross Power – 36.4 kW (48.8 hp) @ 2600 rpm
- ✓ Yanmar / 4TNV88 / Stage 3A
- ✓ 142 Nm (105 ft.-lbs.) @ 1600 rpm max torque
- ✓ 2794 mm (110") height to hinge pin
- ✓ 1346 mm (53") machine width - less bucket
- ✓ 2087 kg (4,601 lbs.) operating weight

R134 SKID LOADER

SPECIFICATIONS

	IMPERIAL	METRIC	
DIMENSIONS	Overall Operating Height - Fully Raised	141.1"	3584 mm
	Height to Hinge Pin - Fully Raised	110"	2794 mm
	Overall Height to Top of ROPS	71.9"	1826 mm
	Overall Length with Bucket (w/o Counterweight)	116.2"	2952 mm
	Dump Angle at Full Height	42°	
	Dump Height - Fully Raised	86.5"	2197 mm
	Dump Reach at Full Height	20.8"	528 mm
	Maximum Rollback Angle at Ground	29°	
	Rollback Angle at Full Height	99°	
	Seat to Ground Height	33.6"	853 mm
	Wheelbase	36.7"	932 mm
	Overall Width - Less Bucket ^A	53"	1346 mm
	Bucket Width	61"	1524 mm
	Ground Clearance to Chassis	8.3"	211 mm
	Overall Length without Bucket (w/o Counterweight)	91.1"	2314 mm
	Rear Departure Angle	29°	
	Clearance Radius – Front with Bucket	69.2"	1758 mm
	Clearance Radius – Front without Bucket	43.4"	1102 mm
	Clearance Radius – Rear (w/o Counterweight)	58.4"	1484 mm
	Standard Specification Tire Size	10.00x16.5 HD	
ENGINE	Make	Yanmar	
	Model	4TNV88 / Stage 3A	
	Gross Power @ 2600 rpm	48.8 hp	36.4 kW
	Net Power @ 2600 rpm	-	-
	Maximum Torque @ 1600 rpm	105 ft.-lbs.	142 Nm
	Displacement	134.3 cu.in.	2.2 L
HYDRAULICS	Auxiliary Hydraulic Flow – Standard	16.4 gpm	62 L/min
	High-Flow Auxiliary Hydraulics - Option	N/A	
	Reservoir Capacity	8 gal.	30 L
ELECTRICAL	Battery	12-volt	720 CCA
	Starter	12-volt	
	Alternator	40-amp	
CAPACITIES / WEIGHTS	Rated Operating Capacity ^B	1,340 lbs.	612 kg
	Fuel Tank	12.4 gal.	47 L
	Travel Speed – Maximum	5.4 mph	8.7 km/hr
	Travel Speed with Two-Speed Option – Maximum	N/A	
	Operating Weight ^C – Approximate	4,601 lbs.	2087 kg

A Overall width is dependent upon the amount of wheel offset

B Per SAE J8181, SAE J732, and ISO 14397

C Weight of base unit with standard equipment, standard tires (heavy-duty flotation), standard dirt-construction bucket and 175 lbs. (79 kg) operator.

Gehl reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Gehl reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.



STANDARD FEATURES

- Control type: Dual T-Bar
- Fuel Gauge
- Warning Lamps and Buzzer – Engine and Hydraulic Oil Temperature
- Battery Charge Indicator Lamp
- Low Oil Pressure Light
- Seatbelt Indicator Lamp
- Coolant Temperature Gauge
- Hourmeter
- Manual-Control Hydrostatic Drive
- ROPS/FOPS – Approved Overhead Guard
- Operator Restraint Bar with Armrests
- Independent Hydraulic Reservoir and Hydraulic Oil Cooler
- Engine Intake Air Pre-Heater Starting Assist
- Seatbelt
- Lift Arm Support Device
- Hydraloc™ System
- Front Work Lights
- Dual, Integral Cleanout Plates
- Vandalism Lock Provisions - Fuel and Engine Cover
- Rear Window
- Acoustical Sound Material and Deluxe Headliner
- Cushion Seat
- Front Auxiliary Hydraulics with 3/4-inch Flat-Faced Couplers
- Visual Hydraulic Filter Indicator
- Power Plug (12 V)



geh.com

One Gehl Way, West Bend, WI 53095

Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT